

Temperature and humidity data logger

LOG210 TC

Item number: 31.1061.02

Variant: white



Function

- With internal sensor for the control of temperature and humidity (measuring range -40...+70°C/0...99%RH) and two external inputs for typ K probes (max. measuring range -150 ... +1370°C)
- Two thermocouple sensors included in delivery (measuring range -40...+150°C)
- Large display and easy to use
- Status- and alarm LED
- Memory for 60.000 records
- MAX/MIN function
- Time marking function
- Usable without software (pre-programmed 5 minutes interval)
- Automatic output as PDF file
- Optional configuration software download
- Selectable storage interval via software (10 seconds up to 24 hours)
- HI/LO alarm
- Motion sensor for shock recording (e.g. change of location or door and windows opening)
- USB interface
- Incl. ISO-Certificate
- Made in Germany

Technical data

Measuring range temperature indoor	-40...+70°C
Measuring range temperature outdoor	External (typ-K) for -40...+1370°C
Delivery contents	Data logger, ISO-Certificate, 2x thermocouple sensors, battery, instruction manual
Measuring range humidity	0 ... 100% r.H.
Power consumption	Battery
Assembling	Wall mounting or freestanding
Batteries included	yes
Batteries	1 x 3,6V ½ AA
Dimensions	(L) 43 (49) x (B) 21 (32) x (H) 92 (98) mm
Weight	57 g